




### touchthefuture...











The EAE group of companies has over 2,200 employees worldwide and EAE reliable products are used in 65 countries, from United Kingdom to Taiwan.

As EAE Technology, we develop value added solutions for international markets in our R&D center. We continue to develop innovative products in smart home and buildings industry, and deliver all our products in accordance with international, open standards such as KNX, DALI, TCP/IP and WiFi.

Using most reliable technologies and platforms, we will always provide highest benefits to all our customers. With our KNX-approved manufacturing and training center, and our consulting and supervisor services, we will continue to achieve uncompromising customer satisfaction, before and after sales...











#### Thermostat

All devices in your home are under your control with Oria thermostats.





#### Switch

Experience life of comfort with Oria switches.



#### Socket

Socket group with eye catching design for perfect harmony.





Control is under your fingertips...


## a simple touch, unlimited comfort thermostats

Expandable up to 4 folds, Oria thermostat provide a wide collection of possibilities for all spaces where both thermostats and programmable switches are needed at the same time.

Oria thermostats can perform all needed operations with a single touch. Programmable buttons on Oria thermostats can control comfort and energy saving needs such as lighting, shutter/blind, scene call, speakers and panic button for you.







2 Fold Pearl White



2 Fold Mustang Gray 3 Fold Pearl White






4 Fold Mustang Gray



2 Fold Anthracite













# a simple touch, unlimited comfort SWITCHES

The new generation of Oria switches adds a simple and elegant touch to the world of users while fulfilling unlimited needs with its design. With rich collection options expandable to 12 buttons in a single frame, enjoy one-point management of on-site lighting, heating-cooling, shutter-blind, speakers, scene call and panic buttons controls.





### Inspired by



Throughout history, pearl has been one of the jewels that is priced due to its warm glow and grace. Many references to pearl can be found in many cultures and mythos. Designed to express this grace, Oria pearl white is eye-catching.



3 Fold Pearl White



Single Pearl White



1 Fold Anthracite



4 Fold Anthracite



**5 Fold** Mustang Gray





6 Fold Pearl White












# Add Value To Your Environment...







#### Antenna Mustang Gray



Socket Anthracite



Data Pearl White



**Antenna** Anthracite



**UPS** Mustang Gray



Data+Socket Pearl White



Antenna+Socket+Data Anthracite



Antenna+Socket+Data Pearl White



#### Antenna+Socket+Data+UPS Mustang Gray




### THE HARMONY OF THERMOSTATS, SWITCHES AND SOCKETS










#### **THERMOSTAT**

#### **TECHNICAL SPECIFICATIONS**



- Can be configured with ETS3 / ETS4 / ETS5.
- Serial thermostat with plastic push-button
- Temperature control via digital LCD
- Internal temperature sensor (°C/°F)
- Adjustable fan speed (1, 2, 3, Automatic)
- Multiple operation modes (Comfort, Night, Outdoor, Indoor)
- Fully automated operation feature (hot-cold transition)
- Control of all HVAC units including VRF-VRV and air conditioning devices
- PI relative, PI on-off (PWM), On/Off, Fan coil, Split unit controls
- Easy installation to 60x60 mm standard switch junctions
- 2 dependent or 4 independent programmable buttons can be programmed for various functions.
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control.
  - Status notification LED

Protection type	IP 20	EN 60529	
Safety class	II	EN 61140	
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line	
	Supply voltage	20 mA	
	Power consumption	20 mA x 30V	
Operation LEDs	Programming LED for each fold	1 to 5 RGB LEDs for physical address identification	
Button operation life	100.000		
Temperature	Operating	-5° C + 45° C	
	Storage	-25° C + 55° C	
	Transport	-25° C + 70° C	
CE	In accordance with EMC guideline and low voltage regulation		






3 Fold Thermostat 4 Fold Thermostat

Dimensions (mm)
2 Fold Thermostat

а	b	n
90	9	90
90	9	111,5
90	9	133


4 Fold

#### **Assembly Detail**



#### Important note!

The distance between the two thermostats should be at least **120 mm** from center to center.




#### SWITCH

#### **TECHNICAL SPECIFICATIONS**




- Can be configured with ETS3 / ETS4 / ETS5.
- Serial switches with plastic push-button
- Large collection option up to 4 Folds
- Product options with and without notification LED
- Optionally, icon branding is available.
- Different color options
- Easy installation to 60x60 mm standard switch junctions
- Channels are identical, each with the following functions;
  - Switching,
  - Dimming,
  - Shutter/Blind control,
  - Value and priority assignment,
  - Scene control,
  - Status notification LED

Protection type	IP 20	EN 60529		
Safety class	II	EN 61140		
Supply	Voltage Range	21-30V DC, Supply from EIB/KNX line		
	Supply voltage	15 mA		
	Power consumption	15 mA x 30V		
Operation LEDs	Programming LED for each fold	1 to 5 RGB LEDs for physical address identification		
Button operation life	100.000			
Temperature	Operating	-5° C + 45° C		
	Storage	-25° C + 55° C		
	Transport	-25° C + 70° C		
CE	In accordance with EMC guideline and low voltage regulation			




Dimensions (mm)	а	b	h
Single Switch	90	9	90
1 Fold Switch	90	9	90
2 Fold Switch	90	9	90
3 Fold Switch	90	9	90
4 Fold Switch	90	9	90
5 Fold Switch	90	9	111,5
6 Fold Switch	90	9	133

#### **Assembly Detail**




#### Important note!

The distance between the two switches should be at least **120 mm** from center to center.



### THERMOSTAT and SWITCH PRODUCT CODE LEGEND



Sample Order Code

Sample Order Code

#### INT-OT2-0101F1

With Icon
With Status
Anthracite Glass Color
Anthracite
2 fold
Thermostat

#### INT-OS2-0300F1

With Icon
With Status
No Glass
Mustang Gray
2 fold
Switch





www.eaetechnology.com | 29

### THERMOSTAT and SWITCH ICON OPTIONS



### SOCKET TYPES



Grounded Socket **01** 



RJ11 07



UPS Socket 02



RJ45 08



TV 03



RJ45-RJ11 **09** 



TV-SAT **04** 



Child-Proof Socket 10



TV-SAT-SAT **05** 




Covered Socket 11



SAT 06

### SOCKET PRODUCT CODE LEGEND



Sample Order Code



### SOME OF OUR REFERENCES









ROUTE ATAKÖY\*

İstanbul



Türk Telekom

TÜRK TELEKOM R&D BUILDING Istanbul



TURKISH AIRLINES DE TÜRK HAVA YOLLARI

TURKISH AIRLINES SIMULATION BUILDING





PRESIDENTIAL SYMPHONY ORCHESTRA BUILDING Ankara















Türk Traktör

TÜRK TRAKTÖR Sakarya - Ankara

\*Ongoing project



**PARK** PARK JÖVEN RESIDENCES\* Ankara





**GARANTI BLOCKS\*** 



top interieur

TOP INTERIEUR FURNITURE Belgium



**PURATOS FOOD** 





DR. LÜTFİ KIRDAR KARTAL TRAINING AND RESEARCH HOSPITAL















B/S/H/

**BSH** Cerkezkoy

### OTHER PRODUCTS





**RCU2018** 

EAE KNX - ROOM CONTROL UNIT



PD100/MD100

EAE KNX - PRESENCE/MOTION SENSOR



**DA100** 

EAE KNX - DALI GATEWAY



SW108

EAE KNX - RELAY MODULE



PSU320/640

EAE KNX - POWER SUPPLY 320mA/640mA



MIO 1616

EAE KNX - MULTI INPUT OUTPUT



#### IPR100

EAE KNX - IP ROUTER



#### **UI108**

EAE KNX - UNIVERSAL INTERFACE



### KINEXA BUILDING MANAGEMENT SYSTEM

All rights reserved. 2018 EAE Teknoloji A.Ş., at its sole discretion, reserves its right to make necessary changes without any prior notice.

For installation, connection and commissioning of a product in the catalog, please refer to the technical documentation of relevant device.







Increase the comfort of your living spaces and reduce your energy costs with KNX System Installation! As intelligent home and building automation systems are becoming more and more widespread, Oria allows you and your living spaces to explore the elegance of technology.







#### EAE Teknoloji A.Ş.

İkitelli Organize Sanayi Bölgesi Eski Turgut Özal Caddesi No:20 Başakşehir / İstanbul - TURKEY Tel. : +90 212 413 21 00 (pbx) Faks: +90 212 549 37 90 www.eaetechnology.com